LIVE OAK
METAL WORKS & SUPPLY
YOUR LAST ROOF NEXT

STANDARD COLOR OPTIONS

Our standard palette of proven Sherwin-Williams WeatherXL™ silicone-modified polyester coatings are specially formulated to reflect the sun's rays before they can be absorbed, keeping your roof cooler than traditional roofing materials and reducing energy use.

Polar White (PW)
SR 65% TE .87 SRI 78

Old Town Gray (OG)
SR 42% TE .87 SRI 47

Charcoal Gray (CG)
SR 36% TE .86 SRI 38

Black CRINKLE (CBK)
SR 30% TE .87 SRI 31

Black (BK)
SR 30% TE .85 SRI 30

Light Stone (LS)
SR 57% .TE 87 SRI 67

Koko Brown (KB)
SR 34% TE .88 SRI 36

Burnished Slate (BS)
SR 32% TE .87 SRI 33

Rustic Red (RR)
SR 39% TE .86 SRI 42

Evergreen (EG)
SR 34% TE .88 SRI 36

Acrylic GALVALUME® (GL)
N/A

- Our metal roofing is manufactured using specially designed coatings to help keep your roof and your home cooler. These coatings ensure that our metal roofing has higher solar reflectivity and higher thermal emissivity.
- **Solar Reflectivity (SR)**: Solar Reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. Solar reflectivity values range from 0 to 1.0, with a value of 0 indicating that the surface absorbs all solar energy and a value of 1.0 indicating total reflectance of the sun's solar energy.
- **Thermal Emissivity (TE)**: Thermal Emissivity or emittance is a measure of a material's ability to release or emit heat so that it stays cool to the touch.
- **Solar Reflectance Index (SRI)**: The Solar Reflectance Index combines solar reflectivity and thermal emissivity into one number. It's a measure of the roof surface's ability to stay cool by reflecting solar radiation and emitting thermal radiation. It's used to determine compliance with LEED and is calculated using values for reflectance and emissivity.
- A 40-year limited paint warranty is available.
- Your final color selection should be made using actual color chips.
- For the most current information, please visit *liveoakmetals.com*.

*Colors displayed are for visual reference only and are not intended to be an exact match. Due to limitations in the CMYK printing process and differences in monitor, browser, and PDF display settings, the color shown may vary from the actual product finish. For accurate color selection, please visit our showroom to review physical product samples and make final color selections.

SHERWIN-WILLIAMS.
Coil Coatings

©2026 Live Oak Metal Works & Supply

Sherwin-Williams® and WeatherXL™ are trademarks of SWIMC LLC.